RBC Merchant Services

Verifone Point-of-Sale Device Comparison Guide

Verifone V210

The Verifone V210 is a durable and portable payment device designed to meet the demands of dynamic business environments. Its compact, ergonomic design fits comfortably in your hand. Ideal for businesses of all sizes, this solution is ready to meet your business needs.



Display	3.5” Color LCD | Capacitive Multi touch Screen | LED Backlight | Resolution 320 | LED Backlight Resolution 320 x 480 HVGA
Multi-media	Speaker
User Interface	Tactile 15 Key Keypad
Printer	18 lps | 40mm Paper Roll
Card Readers	Magstripe ISO 7810, 7811, 7813 | Smart Card EMVCo Approved
Contactless	EMVCo Approved | Supports Major NFC and Contactless Schemes
Connectivity	3G/4G | Bluetooth® v4.2 | WiFi 2.4GHz
Security	PCI PTS 6.x Approved
Connections	Charging and Data Contacts | USB Type-C
Power	Adapter 5VDC, 2.2A | Battery 3.7V, 3100mAh Li-ion | Field Replaceable Ion | Rating 5V, 2.2A, DC Jack
Physical	173mm L x 80mm W x 60mm H | Weight 371g
Environmental	Operating Temperature 0 to 50 C (32 to 122 F) | Storage Temperature -20 to 60 C (-4 to 140 F) Relative Humidity 5% to 90%, Non-condensing

Verifone e235

Designed for effortless handheld use, the compact yet powerful RBC EZPay Verifone e235 payment device adapts to your business needs. Ideal for small businesses, taxi, delivery services, and beyond, it combines practicality with durability.



Display	2.3” Color LCD | LED Backlight | Resolution: 240 x 296
Multi-media	Speaker
User Interface	Tactile 15 Key Keypad
Card Readers	Magstripe ISO 7810, 7811, 7813 | Smart Card EMVCo Approved
Contactless	EMVCo Approved | Supports Major NFC and Contactless Schemes
Connectivity	Bluetooth® v4.2 | WiFi 2.4GHz
Security	PCI PTS 6.x Approved
Connections	Charging and Data Contacts | USB Type-C
Power	Battery 3.7V, 2800mAh Li-ion | Rating 5V, 2A, USB Type-C
Physical	136 mm L x 70 mm W x 18 mm H | Weight: 210g
Environmental	IP Rating IP53 | Operating Temperature - 10° to 50° (14° to 122° F) Charging Temperature 0° to 45° C (32° to 113° F) Storage Temperature -20° to 55° C (-4° to 131° F) Relative Humidity 5% to 90%, Non-condensing

Disclaimer

The content of this publication is for the general guidance and benefit of our clients. While efforts are made to ensure the accuracy and completeness of the information at the time of publication, errors and omissions may occur. You should not act or rely on the information herein without seeking the advice of a professional. RBC Royal Bank (Aruba) N.V. and its affiliates specifically disclaim any liability which is incurred as a consequence, directly or indirectly, of the use and application of any of the contents of this publication. RBC Royal Bank (Aruba) N.V. reserves the right to amend the content stated in this publication.

® / ™ Trademark(s) of Royal Bank of Canada. Used under license. ‡ Trademark(s) are the property of their respective owner(s). All other trademarks are the property of their respective owner(s).